

[54] **COMPUTER-TELEPHONE INTERFACE METHOD AND APPARATUS**

[76] Inventor: David L. Danner, 1806 T St., N.W., Washington, D.C. 20009

[21] Appl. No.: 36,333

[22] Filed: Apr. 9, 1987

[51] Int. Cl.⁴ H04M 11/00; H04M 1/56

[52] U.S. Cl. 379/96; 379/354

[58] Field of Search 379/96, 97, 98, 354

[56] **References Cited**

U.S. PATENT DOCUMENTS

| | | | |
|-----------|--------|-----------------|-----------|
| 4,291,198 | 9/1981 | Anderson et al. | 379/354 X |
| 4,431,870 | 2/1984 | May et al. | 379/354 X |
| 4,524,244 | 6/1985 | Faggin et al. | 379/96 X |
| 4,640,989 | 2/1987 | Riner et al. | 379/96 X |
| 4,660,218 | 4/1987 | Hashimoto | |

OTHER PUBLICATIONS

Baizcomp, Sunnyvale, Calif. Brochure Entitled "There's Only One PC/XT Modem Designed To Let Both You and Your Computer Talk," received 3/11/85.

Telecommunications, "Professional Workstation: Prod-

ucts Feature Zaisan, Inc. Houston Texas," p. 114, of Sep. 1984 issue.

Primary Examiner—Keith E. George

Attorney, Agent, or Firm—Rogers & Killeen

[57] **ABSTRACT**

A method and apparatus for a computer-telephone interface system by which a general purpose personal computer is enabled to perform telephone functions such as dialing, answering ringing lines, and placing lines on hold without the need for a separate telephone instrument. The interface system is responsive to digital signals received from a microprocessor in the computer to implement the signalling functions utilized in a standard switched telephone network. The interface system performs dialing sequences entered either from the keyboard of the computer, a location in the computer memory, a location on a display screen associated with the computer or a location specified by a cursor used in association with the keyboard. Operation of the interface system does not interfere with the concurrent operation by the computer of an applications program.

21 Claims, 4 Drawing Sheets

